Vert exaggeration = 5.0 Datum = 76.0 Link Name 1.001 1.002 1.000 Section Type 150mm 225mm 225mm Slope (1:X) 1:200.0 1:200.0 1:200.0 Cover Level (m) Invert Level (m)

37.225

47.463

41.694

INFORMATION

discrepancies before work proceeds.

Length (m)

© ORS
This drawing and any design hereon is the copyright of the
Consultants and must not be reproduced without their written consent.
All drawings remain the property of the Consultants.

All drawings remain the property of the Consultants.

Figured dimension only to be taken from this drawing.
All dimensions to be checked on site.

Consultants to be informed immediately of any

REV NO:	DATE:	REVISION NOTE:	DWN BY:	CKD BY:
P01	23/01/2024	ISSUED FOR PLANNING	PMC	МН

CLIENT:	WESTMEATH COUNTY COUNCIL								
PROJECT:	PROPOSED SERVICED SITES DEERPARK, CASTLEPOLLARD, CO. WESTMEATH								
TITLE:	FOUL SEWER LONGITUDINAL SECTIONS								
DRAWN:	CHECKED:		APPROVED:	JOB NO:	REV:				
PMC	RD		MH	230894	D01				
DATE: OCT. 2023			00	DRAWING NO: 230894-ORS-Z1-ZZ-DR-CE-410	P01	Т			



ISO 9001:2015 QUALITY ASSURED COMPANY

GENERAL NOTES

1. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH ALL RELEVANT ENGINEER'S AND ARCHITECT'S DRAWINGS

2. ALL LEVELS ARE IN METRES TO ORDNANCE DATUM, MALIN

3. THE POSITION OF EXISTING SERVICES AS SHOWN ON THE DRAWING MAY NOT BE ACCURATE. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR LOCATING ALL EXISTING SERVICES ON THE SITE AND SHOULD CONTACT THE RESPECTIVE UTILITY PROVIDERS AND AUTHORITIES FOR THE MOST UP-TO-DATE INFORMATION BEFORE

4. EXISTING LEVELS ARE INDICATIVE ONLY AND MUST BE CHECKED AND VERIFIED ON SITE PRIOR TO

5. PROPOSED MANHOLE COVER LEVELS ARE APPROXIMATE AND SHOULD BE ADJUSTED TO SUIT LOCAL FINISHES.

6. ALL SURFACE WATER DRAINAGE INFRASTRUCTURE SHALL BE CONSTRUCTED IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS.

8. GULLY POSITIONS ARE APPROXIMATE ONLY AND SHOULD BE LOCATED AT LOW POINTS.

DRAINAGE, STRIP DRAINS AND GULLY TRAPS BENEATH

10. WHERE IT IS NOT POSSIBLE TO ACHIEVE MINIMUM COVER, PIPES SHOULD BE BEDDED AND SURROUNDED IN

CONCRETE 150MM THICK, CLASS E IN ACCORDANCE WITH TII STANDARD CONSTRUCTION DETAIL CC-SCD-00521.

11. ALL WASTEWATER DRAINAGE INFRASTRUCTURE SHALL BE CONSTRUCTED IN ACCORDANCE WITH IRISH WATER STANDARDS. REFER TO IRISH WATER PUBLICATIONS "WASTEWATER INFRASTRUCTURE STANDARD DETAILS - IW-CDS-5030-01" AND "CODE OF PRACTICE FOR

WASTEWATER INFRASTRUCTURE - IW-CDS-5030-03"

12. HYDRANTS TO BE ACCORDANCE WITH IRISH WATER STANDARD DETAILS STD-W-16 TO STD-W-19.

13. THRUST BLOCK ARRANGEMENTS SHALL COMPLY WITH IRISH WATER STANDARD DETAILS STD-W-28

14. REFER TO MECHANICAL AND ELECTRICAL ENGINEER'S DRAWINGS FOR INTERNAL DRAINAGE AND DETAILS OF SOIL AND VENT PIPES LEADING TO WASTEWATER DRAINAGE

15. ALL WATER INFRASTRUCTURE SHALL BE CONSTRUCTED IN ACCORDANCE WITH IRISH WATER STANDARDS. REFER TO IRISH WATER PUBLICATIONS "WATER INFRASTRUCTURE STANDARD DETAILS - IW-CDS-5020-01" AND "CODE OF PRACTICE FOR WATER INFRASTRUCTURE - IW-CDS-5020-03"
16. ALL PLANTING & TREES TO COMPLY WITH SEPERATION DISTANCES AS PER IRISH WATER STANDARD DETAILS FOR WASTEWATER, STD-WW-06 AND STD-WW-06A AND FOR

17. A METHOD STATEMENT SHALL BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION AND TESTING18. ALL PIPE DIAMETERS INDICATED ARE INNER DIAMETER.

19. THESE DRAWINGS ARE NOT TO BE USED FOR SETTING OUT PURPOSES. REFER TO ARCHITECTS DRAWINGS FOR

WATER, STD-W-12 AND STD-W-12A

SETTING OUT.

7. LOCKABLE TYPE GULLY TRAPS TO BE USED ON ALL

9. REFER TO ARCHITECTS' DRAWINGS FOR ALL ROOF

AND SPECIFICATIONS.

COMMENCING THE WORKS.

SURFACE WATER DRAINS.

DOWNPIPES.

COMMENCEMENT.

HEAD UNLESS NOTED OTHERWISE.